



Signtech Handels GmbH

Halbgasse 1; A -1070 Wien Austria

Tel.: +43 (0) 720303032 - 10

Fax: +43 (0) 720303032 - 99 EORI ATEOS1000031704

Mobil: +43 (0) 676 95 35 745 UID ATU66399756

www.e²ke²entechnik.com office@etikettentechnik.com

TECHNICAL DATA Godex ZX1200i * ZX1300i ** ZX1600i ***

Printing method	Thermotransfer / Thermodirekt
Resolution	203 dpi (12 Dots/mm) * 300 dpi (12 Dots/mm) ** 600 dpi (24 Dots/mm) ***
Printing speed	10 ips (254mm/s) * 7 ips (177 mm/s) ** 4 ips (102 mm/s) ***
Print width	4.09" (104mm) Up to (108mm) * 4.09" (104mm) Up to (105.7mm) ** 4.09" (104mm) Up to (105.6mm) ***
Print length	Min. 0.16" (4 mm) ; Max . 180" (4572mm) * Min. 0.16" (4 mm) ; Max. 85"(2159 mm) ** Min. 0.16" (4 mm) ; Max. 26"(660 mm) ***
Processor	32-bit RISC CPU
Memory	Flash: 128 MB Flash (60 MB für User), SDRAM: 32 MB
Interfaces	USB 2.0 (B-Type),Serieller Port,Ethernet port (RJ-45),3 x USB Host (Type A)
Ribbon	Length Max. 1476' (450 m) Width Min. 1.18" (30 mm) – Max. 4.33" (110 mm) Core diameter 1" (25.4 mm)
Control panel	3.2" LCD-Touchscreen On/off button with green LED backlighting Control keys: FEED / PAUSE / CANCEL with Dual-color LED backlight: Ready (Green); Error (Red) Calibration button (backside)